

Technical Data Sheet

QUICK DRYING STAIN BLOCK

Product Code: 21380 Enamels/ Sealers and Stain Covers



DESCRIPTION

Synthetic stain block sealer based on special resins. Especially recommended to remove and hide difficult stains on walls and ceilings.

USE: INTERIOR

Recommended to isolate, cover and hide stains caused by moisture, grease, nicotine or smoke on walls and ceilings. Product can be applied without prior priming on well consolidated and dry surfaces such as plaster, drywalls and gypsum.

PROPERTIES

- Excellent bright white colour
- High opacity level
- Excellent hiding power
- Blocks and covers stains
- Repaintable with any type of waterbased or synthetic emulsions
- Breathable
- Easy application
- Quick drying

Finish: Matt

Colour: WHITE

Viscosity: Minimum 35 P S/FR1007

Density: 1,62 ± 0,05 g/cc S/FR1001

Drying: Touch dry in 30 minutes

Minimum repaint time: 2 hours

Thinner: JUNO D-45

Coverage: 8 m²/L (per coat)

Flash Point: 13 °C

VOC Content : Maximum 450 g/l

21380 WHITE



Format: 0,750L / 4 L

Technical Data Sheet

QUICK DRYING STAIN BLOCK



Product Code: 21380 Enamels/ Sealers and Stain Covers

SURFACE PREPARATION

UNTREATED SURFACES. On new, clean, dry and firm surfaces, no prior prep work is required. In case of needing improved consistency or adhesion, seal and prime with a coat of **Akril-80 (42.115)**.

PAINTED SURFACES. If existing paint is in good condition, product can be applied directly. For deteriorated paint, eliminate loose and flaking paint, and any dust or dirt.

For gloss or satin surfaces sand lightly to remove gloss to improve surface adhesion and eliminate substrate surface tension.

Before proceeding with the paint job, carry out a test on a small area to verify the finish and surface adhesion as well as product compatibility between coats.

PATHOLOGIES.

Mould contamination. Wash thoroughly and disinfect using **Junoclean Prod.Code 760.180**. Rinse with water and leave to dry out completely.

Saline efflorescence (Saltpeter). Brush vigorously, clean and neutralize with a mixture of Chloridic acid or Zinc Sulphate (10%) and water. Rinse with water and leave to dry out completely.

GENERAL RECOMMENDATIONS

Stir contents well ensuring complete homogenization.

Apply on consistent, clean and completely dry surfaces, free from efflorescence (saltpeter) and mould.

Do not apply on surfaces with temperatures below 5°C, nor on excessively warm surfaces.

APPLICATION METHOD. Brush or roller. For improved results, apply two coats, first one diluted with 10% **D-45 Thinner (Prod.Code 50.017)** and the second coat undiluted.

CLEANING. Clean up stains and work tools using **D-45 JUNO Universal Thinner (Product Code 50.017)**.

OBSERVATIONS

Avoid topcoating with waterbased emulsions before fully curing (10 days), as the water content in the paint will bring out old stains.

SAFETY AND ENVIRONMENT

Solvent based product must be applied ensuring proper ventilation and by applying necessary protection measures.

Avoid sources of ignition. Minimize product waste by estimating the amount needed, taking into account the m², porosity and texture of the substrate.

Store surplus paint in a ventilated, dry place. The container must be clean and of adequate size for the quantity of surplus left over. Close containers carefully and keep upright to avoid spills.

Keep the containers away from frost, high temperatures and direct exposure to the sun. Recover unused product for new use to reduce environmental effects. Do not eat, drink or smoke while preparing and applying the product.

Surface preparation and application operations must be carried out with appropriate safety measures. For more information consult the Material Safety Data Sheet.

In case of contact with eyes, rinse with plenty of clean water. Keep out of the reach from children. Do not discharge into drains or the environment.

Dispose to an authorized waste collection point. Consult your council about the correct recycling of both packaging and waste and leftover paint according to law and principles of environmental respect.

The information contained in this data sheet may vary and must be updated. Please visit www.junopaints.com or consult with your nearest JUNO representative who will provide you with the most recent data sheet. Our technical instructions and advice whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, they must only be interpreted as indications WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the intended procedures and purposes. The application, use and processing of the products supplied by JUNO are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.

Industrias JUNO, S.A. • Barrio Sakoni, 10 • 48950 Erandio, Spain • Tel.: +34 944 670 062 • infoweb@juno.es • www.junopaints.com

June 2016 Rev. 04

2 / 2