

TECHNICAL DATA SHEET

AQUASELL Interior/Exterior Acrylic Universal Primer/Sealer

Code: 21.203

JULY 2008

DESCRIPTION

High quality primer/sealer based on aqueous-dispersed acrylic resins and selected pigments. Formulated to meet the performance requirements of residential and commercial markets. Provides outstanding filling power and high sealing capacity on absorbent surfaces. Excellent adhesion.

USAGE: INTERIOR - EXTERIOR

Recommended as an undercoat for use on properly prepared interior or exterior masonry, plaster, wallboard, cement, brick, cement composition board, and wall coverings. Product specially conceived for projected plasters, where important absorption differences are found, and facilitates obtaining good finish on difficult areas.

SURFACE PREPARATION

MASONRY

Surfaces must be clean, dry (less than 15% moisture) and efflorescence-free. It is recommended to neutralise concrete and cement surfaces with 10% Hydrochloric Acid, or vinegar. Rinse with water and allow to dry. In case of pre-painted surfaces, any paint in poor condition must be removed. Deteriorated and chipped areas to be treated with Juno Plaste, before the paint is applied. Then, treat as a new surface. Gloss or satin paints or varnishes must be sanded down until the gloss is removed, to improve bonding and remove stresses.

APPLICATION

Apply with a high quality brush, roller, paint pad, or by spray equipment. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. Dilute with water, with a recommended 10% in volume. It is not advisable to add more than 25% of water in volume. Dying: Use Junoral Colorant with water, at ratios not exceeding 3%. Clean-up: With water. Repainting: Any plastic paint can be used.

OBSERVATIONS

Stir thoroughly before using and occasionally when in use. Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website. Plaster before applying Aquasell. If not possible, seal the plaster with Aquasell once dry and sanded. Drying is important to stain-blocking properties. For maximum stain resistance, allow 24 hours before applying topcoat. If drying conditions are poor (low temperature, high humidity), longer drying times are required to achieve full sealing properties.

APPLICATION RECOMMENDATIONS

Surfaces must be clean of dust, grease, oils, dirt, rust, waste or anything else that may contaminate the paint. Remove the paint, varnishes or old treatments in a poor state and if needed clean up the imperfection, area and exposition with an adequate filler. Shake the container before application to homogenize the paint and the color. Respect the recommended application temperature and the drying times between coats (20°C, relative humidity 65%). The thickness of application, temperature and humidity may affect drying times. Buy only the necessary quantity required, taking into account the m², porosity and support texture. Store the remaining product in a dry and well-ventilated place. Work with the appropriate ventilation and respect the safety precautions norms indicated in the safety data sheet of the product

Finish: Matt

Color: White

Density: 1,45 +/- 0,05 S/FR1001

Drying time: 1-2 hours to the touch
Repair: Minimum 12 hours.
Maximum: undefined

Diluent: Water

VOC content: Maximum 30 g/l.

Solids in Volume: 42% (Theoretical)

Performance : 4-8 m² / L/ Coat

Health & Safety: Waterborne product.
Exempt from labelling


CLEANING

Clean the splash and stains immediately with soap water or with an adequate solvent.

Clean tools after use (brushes, rollers, pencils, machines etc.) and let them dry before storing.

Consult your town council about the appropriate recycling method for container, waste and excess paint, in accordance with the existing legislation and environmental protection principles.

SHIPPING

 **Packaging:** 4 & 15 liters
Shipping Weight:
Units per pallet: 150/33

 **Freight Classification:**
 Paint or paint related material

 **Transport Information**
 No restriction for transport (ADR/RID, IMDG, IATA)



The information contained in this data sheet may vary and must be updated. Please visit www.juno.es or consult with your nearest JUNO representative who will provide you with the most recent date sheet. Our technical instructions and advice whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, they must only be interpreted as indications WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the intended procedures and purposes. The application, use and processing of the products supplied by JUNO are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this would be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.