



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: PAVIMYC HB SUELOS 2-C (COMPONENTE B) BLANCO Y COLORES - Código - 07956 (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Industrial paint. For professional user/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

INDUSTRIAS JUNO, S.A.
Barrio Sakonj, 10
48950 ERANDIO - Vizcaya - España
Phone.: +34 944 670 062 - Fax: +34 944 675 832
laboratorio@juno.es
www.juno.es

1.4 Emergency telephone number: +34 944 670 062 (8:00 -15:00)

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity, Category 4, H302+H332

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Dam. 1: Serious eye damage, Category 1, H318

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Corr. 1B: Skin corrosion, Category 1B, H314

Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects

Flam. Liq. 3: H226 - Flammable liquid and vapour

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage

Skin Sens. 1: H317 - May cause an allergic skin reaction

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280: Wear protective gloves/protective clothing/eye protection/face protection

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P501: Dispose of contents/container according to the separated collection system used in your municipality

Substances that contribute to the classification

Formaldehyde, polymer with benzenamine, hydrogenated (CAS: 135108-88-2); Benzyl alcohol (CAS: 100-51-6); 2,4,6-tris (dimethylaminomethyl)phenol (CAS: 90-72-2); 4,4'-methylenebis(cyclohexylamine) (CAS: 1761-71-3)

Acute Toxicity Estimate (ATE mix):

0 % (oral), 52,7 % (dermal), 57,7 % (inhalation) of the mixture consists of ingredient(s) of unknown toxicity

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of pigments and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 135108-88-2 EC: Non-applicable Index: Non-applicable REACH: 01-2119983522-33-XXXX	Formaldehyde, polymer with benzenamine, hydrogenated <input type="checkbox"/> ¹ <input type="checkbox"/>	Self-classified	25 - <45 %
	Regulation 1272/2008 Acute Tox. 4: H302; Skin Corr. 1B: H314 - Danger		
CAS: 100-51-6 EC: 202-859-9 Index: 603-057-00-5 REACH: 01-2119492630-38-XXXX	Benzyl alcohol <input type="checkbox"/> ¹ <input type="checkbox"/>	Self-classified	25 - <45 %
	Regulation 1272/2008 Acute Tox. 4: H302+H332; Eye Irrit. 2: H319 - Warning		
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH: 01-2119486773-24-XXXX	Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 <input type="checkbox"/> ¹ <input type="checkbox"/>	ATP ATP01	1 - <10 %
	Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336; EUH066 - Danger		
CAS: 90-72-2 EC: 202-013-9 Index: 603-069-00-0 REACH: 01-2119560597-27-XXXX	2,4,6-tris(dimethylaminomethyl)phenol <input type="checkbox"/> ¹ <input type="checkbox"/>	ATP CLP00	1 - <10 %
	Regulation 1272/2008 Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning		
CAS: 1761-71-3 EC: 217-168-8 Index: Non-applicable REACH: 01-2119541673-38-XXXX	4,4'-methylenebis(cyclohexylamine) <input type="checkbox"/> ¹ <input type="checkbox"/>	Self-classified	1 - <10 %
	Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Chronic 2: H411; Skin Corr. 1A: H314; Skin Sens. 1: H317; STOT RE 2: H373 - Danger		

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.



SECTION 4: FIRST AID MEASURES (continued)

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

- CONTINUED ON NEXT PAGE -



SECTION 7: HANDLING AND STORAGE (continued)

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

- Minimum Temp.: 5 °C
- Maximum Temp.: 30 °C
- Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

There are no occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	47 mg/kg	Non-applicable	9,5 mg/kg	Non-applicable
	Inhalation	450 mg/m ³	Non-applicable	90 mg/m ³	Non-applicable
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,31 mg/m ³	Non-applicable
4,4'-methylenebis(cyclohexylamine) CAS: 1761-71-3 EC: 217-168-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	25 mg/kg	Non-applicable	5 mg/kg	Non-applicable
	Dermal	28,5 mg/kg	Non-applicable	5,7 mg/kg	Non-applicable
	Inhalation	40,55 mg/m ³	Non-applicable	8,11 mg/m ³	Non-applicable
4,4'-methylenebis(cyclohexylamine) CAS: 1761-71-3 EC: 217-168-8	Oral	Non-applicable	Non-applicable	0,06 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,06 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,21 mg/m ³	Non-applicable

PNEC:

Identification			
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	STP	39 mg/L	Fresh water
	Soil	0,456 mg/kg	Marine water
	Intermittent	2,3 mg/L	Sediment (Fresh water)
	Oral	Non-applicable	Sediment (Marine water)
			1 mg/L
			0,1 mg/L
			5,27 mg/kg
			0,527 mg/kg

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	STP	0,2 mg/L	Fresh water	0,084 mg/L
	Soil	Non-applicable	Marine water	0,0084 mg/L
	Intermittent	0,84 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
4,4'-methylenebis(cyclohexylamine) CAS: 1761-71-3 EC: 217-168-8	STP	80 mg/L	Fresh water	0,008 mg/L
	Soil	0,072 mg/kg	Marine water	0,0008 mg/L
	Intermittent	0,08 mg/L	Sediment (Fresh water)	0,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,039 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Filter mask for gases, vapours and particles	CE CAT III	EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
	NON-disposable chemical protective gloves	CE CAT III	EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Face shield	CE CAT II	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CE CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CE CAT III	EN ISO 13287:2012 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	5 % weight
V.O.C. density at 20 °C:	52,48 kg/m ³ (52,48 g/L)
Average carbon number:	9
Average molecular weight:	120 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	Non-applicable
EU limit for the product (Cat. A.J):	500 g/L (2010)
Components:	Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	200 °C
Vapour pressure at 20 °C:	28 Pa
Vapour pressure at 50 °C:	214,18 Pa (0,21 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	1049,5 kg/m ³
Relative density at 20 °C:	1,05
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Decomposition temperature: Non-applicable *
Melting point/freezing point: Non-applicable *
Explosive properties: Non-applicable *
Oxidising properties: Non-applicable *

Flammability:

Flash Point: 41 °C
Flammability (solid, gas): Non-applicable *
Autoignition temperature: 436 °C
Lower flammability limit: Not available
Upper flammability limit: Not available

Explosive:

Lower explosive limit: Non-applicable *
Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable *
Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- CONTINUED ON NEXT PAGE -



**PAVIMYC HB SUELOS 2-C (COMPONENTE B) BLANCO Y
COLORES - Código - 07956 (B)**



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.
- B- Inhalation (acute effect):
 - Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Non-applicable
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	500 mg/kg	Rat
	LD50 dermal	2500 mg/kg (ATEi)	
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	LD50 oral	1200 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Formaldehyde, polymer with benzenamine, hydrogenated CAS: 135108-88-2 EC: Non-applicable	LD50 oral	500 mg/kg (ATEi)	
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	LD50 oral	480 mg/kg	
4,4'-methylenebis(cyclohexylamine)	LD50 dermal	Non-applicable	Rat
CAS: 1761-71-3	LC50 inhalation	Non-applicable	
EC: 217-168-8			

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	541,88 mg/kg (Calculation method)	0 %
Dermal	18920 mg/kg (Calculation method)	52,7 %
Inhalation	11 mg/L (4 h) (Calculation method)	57,7 %

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	LC50	646 mg/L (48 h)		
Benzyl alcohol	EC50	400 mg/L (24 h)	Leuciscus idus	Fish
CAS: 100-51-6	EC50	79 mg/L (3 h)	Daphnia magna	Crustacean
EC: 202-859-9	EC50	79 mg/L (3 h)	Scenedesmus subspicatus	Algae
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7	LC50	1 - 10 mg/L (96 h)		Fish
CAS: 64742-95-6	EC50	1 - 10 mg/L		Crustacean
EC: 265-199-0	EC50	1 - 10 mg/L		Algae
2,4,6-tris(dimethylaminomethyl)phenol	LC50	345 mg/L (96 h)	QSAR	Fish
CAS: 90-72-2	EC50	Non-applicable		
EC: 202-013-9	EC50	Non-applicable		
4,4'-methylenebis(cyclohexylamine)	LC50	67.8 mg/L (96 h)	Leuciscus idus	Fish
CAS: 1761-71-3	EC50	2.5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 217-168-8	EC50	Non-applicable		

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
	BOD5	Non-applicable	Concentration	100 mg/L
Benzyl alcohol	COD	Non-applicable	Period	14 days
CAS: 100-51-6	BOD5/COD	Non-applicable	% Biodegradable	94 %
EC: 202-859-9	BOD5	0.19 g O2/g	Concentration	Non-applicable
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7	COD	0.44 g O2/g	Period	Non-applicable
CAS: 64742-95-6	BOD5/COD	0.43	% Biodegradable	Non-applicable
EC: 265-199-0				

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	BCF	0
Benzyl alcohol	Pow Log	1.1
CAS: 100-51-6	Potential	Low
EC: 202-859-9	BCF	
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7	Pow Log	4
CAS: 64742-95-6	Potential	
EC: 265-199-0	BCF	3
2,4,6-tris(dimethylaminomethyl)phenol	Pow Log	0.77
CAS: 90-72-2	Potential	Low
EC: 202-013-9		

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc	Non-applicable	Henry	Non-applicable
Benzyl alcohol	Conclusion	Non-applicable	Dry soil	Non-applicable
CAS: 100-51-6	Surface tension	3,679E-2 N/m (25 °C)	Moist soil	Non-applicable
EC: 202-859-9				

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	Koc	15130	Henry	9,312E-12 Pa·m ³ /mol
	Conclusion	Immobilized	Dry soil	No
	Surface tension	Non-applicable	Moist soil	No

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP6 Acute Toxicity, HP8 Corrosive

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



- 14.1 UN number:** UN3470
- 14.2 UN proper shipping name:** PAINT, CORROSIVE, FLAMMABLE
- 14.3 Transport hazard class(es):** 8
- Labels:** 8, 3
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: 163, 367
- Tunnel restriction code: D/E
- Physico-Chemical properties: see section 9
- Limited quantities: 1 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 38-16:



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN3470
- 14.2 UN proper shipping name:** PAINT, CORROSIVE, FLAMMABLE
- 14.3 Transport hazard class(es):** 8
- Labels: 8, 3
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: 163, 367
- EmS Codes: F-E, S-C
- Physico-Chemical properties: see section 9
- Limited quantities: 1 L
- Segregation group: Non-applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2019:



- 14.1 UN number:** UN3470
- 14.2 UN proper shipping name:** PAINT, CORROSIVE, FLAMMABLE
- 14.3 Transport hazard class(es):** 8
- Labels: 8, 3
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Benzyl alcohol.
 Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Article 95, REGULATION (EU) No 528/2012: Benzyl alcohol (Product-type 6)
 REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c		5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):



SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- “whoopee” cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

‘For professional users only’.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements

Texts of the legislative phrases mentioned in section 2:

- H314: Causes severe skin burns and eye damage
- H412: Harmful to aquatic life with long lasting effects
- H318: Causes serious eye damage
- H317: May cause an allergic skin reaction
- H302+H332: Harmful if swallowed or if inhaled
- H226: Flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- Acute Tox. 4: H302 - Harmful if swallowed
- Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
- Eye Irrit. 2: H319 - Causes serious eye irritation
- Flam. Liq. 3: H226 - Flammable liquid and vapour
- Skin Corr. 1A: H314 - Causes severe skin burns and eye damage
- Skin Corr. 1B: H314 - Causes severe skin burns and eye damage
- Skin Irrit. 2: H315 - Causes skin irritation
- Skin Sens. 1: H317 - May cause an allergic skin reaction
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)
- STOT SE 3: H336 - May cause drowsiness or dizziness

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION (continued)

Classification procedure:

Skin Corr. 1B: Calculation method
 Aquatic Chronic 3: Calculation method
 Eye Dam. 1: Calculation method
 Skin Sens. 1: Calculation method
 Acute Tox. 4: Calculation method
 Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
 IMDG: International maritime dangerous goods code
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organisation
 COD: Chemical Oxygen Demand
 BOD5: 5-day biochemical oxygen demand
 BCF: Bioconcentration factor
 LD50: Lethal Dose 50
 LC50: Lethal Concentration 50
 EC50: Effective concentration 50
 Log-POW: Octanol-water partition coefficient
 Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -