

# Technical Data Sheet

## J-35 EXTRA-MATT WHITE

Product Code: 72205 Interior



### DESCRIPTION

Extra-matt waterbased emulsion paint of excellent quality, based on acrylic copolymers. Offers easy application with a finish that conceals any imperfections on the painted surface due to its extra matt finish. Very good washability. Ideal to decorate and protect any types of interior surfaces. Contains anti-mould protection.

### USE: INTERIOR

Recommended for general use in construction and decoration, especially on walls and ceilings where an extra-matt high quality finish with anti-mold properties is required.

### FEATURES

- Extra-matt finish
- High opacity
- Bright white finish
- Perfect adhesion
- Hides surface imperfections
- High wet-rub resistance
- Does not splash
- Quick drying

**Finish:** Extra-Matt

**Color:** White

**Viscosity:** Min. 130 P S/FR1007

**Density** 1,55 ± 0,05 g/cc S/FR1001

**Drying time:** Touch dry 45 mins.

**Min. re-paint time:** 6 hours

**Maximum re-coat time:** Unlimited

**Thinner:** " Water (max. 10%)

**Performance:** 10-12 m<sup>2</sup>/L (per coat)

Average observed values. Variable depending on texture and absorption

**Tinting:** Juno Universal colorant (max 3%)

**Solids in volume:** 43,8 ± 2 % Theoretical-White

**Flash-point:** Non- flammable

**VOC Content:** Max. 30 g/l

72205 WHITE



**Packaging:** 4L / 15 L

# Technical Data Sheet

## J-35 EXTRA-MATT WHITE

Product Code: 72205 Interior



### SURFACE PREPARATION

**UNTREATED SURFACE.** On new, firm, clean and dry surfaces, no preparation of the substrate is necessary. For added consistency and dustproofing, prime with a coat of diluted Hidrocril Sealer (Prod. Code 81.006) (1 part Hidrocril : 4 parts Water).

On projected plasters, due to varying levels of absorption it is recommended to seal the surface applying 1 coat of **Aquasell (Prod. Code 21.203)**.

**PAINTED SURFACES.** If the paint is in good condition, apply the product directly. For paint in poor condition, remove loose flaking paint, dust and dirt. Go over defective areas, repairing cracks and irregularities with **Juno Repair Plaster (Prod. Code 77.000)** before painting.

On glossy surface paints and varnishes it is necessary to sand the surface to eliminate any gloss to favour adhesion and eliminate surface tension. Paint out a small test patch to check the strength and anchoring of the paint and prevent possible incompatibilities with previous coats/applied paints.

**PATHOLOGIES Mould contamination.** Wash mould stains thoroughly and disinfect using **Junoclean Anti-Mould wash (Prod. Code 760.180)**. Rinse with clean water and let dry completely. Coat using paint with anti-mould additive or add JUNO's **Misky-Misky anti-mould additive (Prod. Code 79.597)**.

**Saline Efflorescence.** Brush thoroughly, clean and neutralize with a Chloridic acid or Zinc Sulphate solution (to 10%). Rinse with water and allow to dry completely before painting.

**Moisture, grease, smoke or nicotine stains, etc.** Clean with water and suitable detergent. Leave to dry completely before applying and priming with **Tapas-Manchas Stain Cover. (Prod.Code 21.350)**.

### APPLICATION TIPS

Stir content thoroughly until complete homogenization. Apply on surfaces that are consistent, clean, completely dry, free of efflorescence (saltpeter) and molds. Do not apply on surfaces with a temperature below 5°C, nor excessively hot surfaces. The need to dilute the product depends on porosity and state of the surface. It is advisable to protect areas that are not going to be painted (plugs, skirting boards, floors, door frames and windows) with painter's tape and paper. Once the work is completed, remove the tape before the paint completely dries, to prevent paint from being pulled off.

**APPLICATION METHOD.** Brush, roller or spray equipment. Apply minimum two coats of J-35.

**CLEANING.** Clean paint stains and work tools immediately after use using soapy water.

### SAFETY AND ENVIRONMENT

Minimize product waste by estimating the amount needed, taking into account the m<sup>2</sup>, porosity and texture of the support. Store any excess material in a ventilated and dry place. The container must be clean and of adequate size for the amount of product left over. Close containers carefully and keep upright to avoid spills. Preserve the containers away from frost, high temperatures and direct exposure to the sun. Recover any unused paint for future use and to reduce environmental effects. Do not eat, drink or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding safety measures. For more information, consult the Safety Data Sheet. In case of contact with eyes wash with clean and abundant water. Keep out of the reach of children. Do not discharge into drains or the environment. Dispose of at an authorized waste collection point. Consult your town hall for correct recycling method for container and waste/leftovers paint according to local legislation and principles of environmental respect.