



**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** DYNAPOK HBAC ALUMINIO 2-C (COMPONENTE B) - Código - 07765 (B)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Anticorrosion primer. For professional user/industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
INDUSTRIAS JUNO, S.A.  
Barrio Sakonj, 10  
48950 ERANDIO - Vizcaya - España  
Phone.: +34 944 670 062 - Fax: +34 944 675 832  
laboratorio@juno.es  
www.juno.es
- 1.4 Emergency telephone number:** +34 944 670 062 ( 8:00 -15:00)

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Acute Tox. 4: Acute toxicity, Category 4, H302+H312+H332  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411  
Asp. Tox. 1: Aspiration hazard, Category 1, H304  
Eye Dam. 1: Serious eye damage, Category 1, H318  
Flam. Liq. 3: Flammable liquids, Category 3, H226  
Skin Corr. 1B: Skin corrosion, Category 1B, H314  
Skin Sens. 1: Sensitisation, skin, Category 1, H317  
STOT RE 2: Specific target organ toxicity if swallowed, repeated exposure, Category 2, H373

- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Danger**



**Hazard statements:**

- Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
- Flam. Liq. 3: H226 - Flammable liquid and vapour
- Skin Corr. 1B: H314 - Causes severe skin burns and eye damage
- Skin Sens. 1: H317 - May cause an allergic skin reaction
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

**Precautionary statements:**

- P101: If medical advice is needed, have product container or label at hand
- P102: Keep out of reach of children
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P501: Dispose of contents/container according to the separated collection system used in your municipality

**Supplementary information:**

Contains Amines, polyethylenepoly-, triethylenetetramine fraction

**Substances that contribute to the classification**



**SECTION 2: HAZARDS IDENTIFICATION (continued)**

Xylene (CAS: 1330-20-7); fatty acids, C16 and C18 unsatd., polymers with bisphenol A, Bu glycidyl ether, epichlorohydrin and triethylenetetramine (CAS: 105839-18-7); 3-aminomethyl-3,5,5-trimethylcyclohexylamine (CAS: 2855-13-2); Benzyl alcohol (CAS: 100-51-6)

**Acute Toxicity Estimate (ATE mix):**

68,01 % (oral), 68,01 % (dermal), 74,08 % (inhalation) of the mixture consists of ingredient(s) of unknown toxicity

**2.3 Other hazards:**

Product fails to meet PBT/vPvB criteria

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\***

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** Mixture composed of pigments and resins

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene</b> <input type="checkbox"/> <sup>1</sup> <input type="checkbox"/> Regulation 1272/2008 Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified <b>10 - &lt;25 %</b>
CAS: 105839-18-7 EC: 600-687-2 Index: Non-applicable REACH: 01-2119983535-26-XXXX	<b>fatty acids, C16 and C18 unsatd., polymers with bisphenol A, Bu glycidyl ether, epichlorohydrin and triethylenetetramine</b> <input type="checkbox"/> <sup>1</sup> <input type="checkbox"/> Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	Self-classified <b>10 - &lt;25 %</b>
CAS: 100-51-6 EC: 202-859-9 Index: 603-057-00-5 REACH: 01-2119492630-38-XXXX	<b>Benzyl alcohol</b> <input type="checkbox"/> <sup>1</sup> <input type="checkbox"/> Regulation 1272/2008 Acute Tox. 4: H302+H332 - Warning	ATP CLP00 <b>1 - &lt;10 %</b>
CAS: 2855-13-2 EC: 220-666-8 Index: 612-067-00-9 REACH: 01-2119514687-32-XXXX	<b>3-aminomethyl-3,5,5-trimethylcyclohexylamine</b> <input type="checkbox"/> <sup>1</sup> <input type="checkbox"/> Regulation 1272/2008 Acute Tox. 4: H302+H312; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	ATP CLP00 <b>1 - &lt;10 %</b>
CAS: Non-applicable EC: 701-188-3 Index: Non-applicable REACH: 01-2119553062-49-XXXX	<b>2-(4-methylcyclohex-3-en-1-yl)propan-2-ol</b> <input type="checkbox"/> <sup>1</sup> <input type="checkbox"/> Regulation 1272/2008 Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	Self-classified <b>1 - &lt;10 %</b>
CAS: 69-72-7 EC: 200-712-3 Index: 607-732-00-5 REACH: 01-2119486984-17-XXXX	<b>Salicylic acid</b> <input type="checkbox"/> <sup>1</sup> <input type="checkbox"/> Regulation 1272/2008 Acute Tox. 4: H302; Eye Dam. 1: H318; Repr. 2: H361d - Danger	ATP ATP13 <b>0,1 - &lt;1 %</b>
CAS: 90640-67-8 EC: 292-588-2 Index: Non-applicable REACH: 01-2119487919-13-XXXX	<b>Amines, polyethylenepoly-, triethylenetetramine fraction</b> <input type="checkbox"/> <sup>1</sup> <input type="checkbox"/> Regulation 1272/2008 Acute Tox. 4: H312; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	Self-classified <b>0,1 - &lt;1 %</b>
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	<b>Ethylbenzene</b> <input type="checkbox"/> <sup>2</sup> <input type="checkbox"/> Regulation 1272/2008 Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	Self-classified <b>&lt;0,1 %</b>
CAS: 107-98-2 EC: 203-539-1 Index: 603-064-00-3 REACH: 01-2119457435-35-XXXX	<b>1-methoxy-2-propanol</b> <input type="checkbox"/> <sup>2</sup> <input type="checkbox"/> Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	ATP ATP01 <b>&lt;0,1 %</b>

<sup>1</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830  
 <sup>2</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

Request medical assistance immediately, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

- CONTINUED ON NEXT PAGE -



**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

- Minimum Temp.: 5 °C
- Maximum Temp.: 30 °C
- Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Environmental limits		
	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>
	IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	IOELV (8h)	100 ppm	375 mg/m <sup>3</sup>
	IOELV (STEL)	150 ppm	563 mg/m <sup>3</sup>

**DNEL (Workers):**

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	47 mg/kg	Non-applicable	9,5 mg/kg	Non-applicable
	Inhalation	450 mg/m <sup>3</sup>	Non-applicable	90 mg/m <sup>3</sup>	Non-applicable
2-(4-methylcyclohex-3-en-1-yl)propan-2-ol CAS: Non-applicable EC: 701-188-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	5 mg/kg	Non-applicable	1,17 mg/kg	Non-applicable
	Inhalation	5,8 mg/m <sup>3</sup>	Non-applicable	5,8 mg/m <sup>3</sup>	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	16 mg/m <sup>3</sup>	Non-applicable
Amines, polyethylenepoly-, triethylenetetramine fraction CAS: 90640-67-8 EC: 292-588-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,57 mg/kg	Non-applicable
	Inhalation	5380 mg/m <sup>3</sup>	Non-applicable	1 mg/m <sup>3</sup>	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	50,6 mg/kg	Non-applicable
	Inhalation	Non-applicable	553,5 mg/m <sup>3</sup>	369 mg/m <sup>3</sup>	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,8 mg/m <sup>3</sup>	Non-applicable
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	25 mg/kg	Non-applicable	5 mg/kg	Non-applicable
	Dermal	28,5 mg/kg	Non-applicable	5,7 mg/kg	Non-applicable
	Inhalation	40,55 mg/m <sup>3</sup>	Non-applicable	8,11 mg/m <sup>3</sup>	Non-applicable
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	Oral	Non-applicable	Non-applicable	0,526 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
2-(4-methylcyclohex-3-en-1-yl)propan-2-ol CAS: Non-applicable EC: 701-188-3	Oral	2,5 mg/kg	Non-applicable	0,42 mg/kg	Non-applicable
	Dermal	2,5 mg/kg	Non-applicable	0,42 mg/kg	Non-applicable
	Inhalation	1,25 mg/m <sup>3</sup>	Non-applicable	1,25 mg/m <sup>3</sup>	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Oral	4 mg/kg	Non-applicable	1 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4 mg/m <sup>3</sup>	0,2 mg/m <sup>3</sup>
Amines, polyethylenepoly-, triethylenetetramine fraction CAS: 90640-67-8 EC: 292-588-2	Oral	20 mg/kg	Non-applicable	0,41 mg/kg	Non-applicable
	Dermal	8 mg/kg	Non-applicable	0,25 mg/kg	Non-applicable
	Inhalation	1600 mg/m <sup>3</sup>	Non-applicable	0,29 mg/m <sup>3</sup>	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m <sup>3</sup>	Non-applicable
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Non-applicable	Non-applicable	3,3 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	18,1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	43,9 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification				
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	STP	39 mg/L	Fresh water	1 mg/L
	Soil	0,456 mg/kg	Marine water	0,1 mg/L
	Intermittent	2,3 mg/L	Sediment (Fresh water)	5,27 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,527 mg/kg
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	STP	3,18 mg/L	Fresh water	0,06 mg/L
	Soil	1,121 mg/kg	Marine water	0,006 mg/L
	Intermittent	0,23 mg/L	Sediment (Fresh water)	5,784 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,578 mg/kg
2-(4-methylcyclohex-3-en-1-yl)propan-2-ol CAS: Non-applicable EC: 701-188-3	STP	2,57 mg/L	Fresh water	0,062 mg/L
	Soil	0,052 mg/kg	Marine water	0,0062 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	0,442 mg/kg
	Oral	16,6 g/kg	Sediment (Marine water)	0,044 mg/kg
Salicylic acid CAS: 69-72-7 EC: 200-712-3	STP	162 mg/L	Fresh water	0,2 mg/L
	Soil	0,166 mg/kg	Marine water	0,02 mg/L
	Intermittent	1 mg/L	Sediment (Fresh water)	1,42 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,142 mg/kg
Amines, polyethylenepoly-, triethylenetetramine fraction CAS: 90640-67-8 EC: 292-588-2	STP	4,25 mg/L	Fresh water	0,19 mg/L
	Soil	19,1 mg/kg	Marine water	0,038 mg/L
	Intermittent	0,2 mg/L	Sediment (Fresh water)	95,9 mg/kg
	Oral	0,18 g/kg	Sediment (Marine water)	19,2 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1,37 mg/kg
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	STP	100 mg/L	Fresh water	10 mg/L
	Soil	5,49 mg/kg	Marine water	1 mg/L
	Intermittent	100 mg/L	Sediment (Fresh water)	52,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	5,2 mg/kg



**8.2 Exposure controls:**

A.- General security and hygiene measures in the work place



As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	 CAT III	EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves	 CAT III	EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.



- CONTINUED ON NEXT PAGE -







**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

**D.- Ocular and facial protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer´s instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer´s instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2012 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	18,37 % weight
V.O.C. density at 20 °C:	257,16 kg/m <sup>3</sup> (257,16 g/L)
Average carbon number:	8,05
Average molecular weight:	107,06 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	360,24 kg/m <sup>3</sup> (360,24 g/L)
EU limit for the product (Cat. A.J):	500 g/L (2010)
Components:	Non-applicable

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Not available
Colour:	 Cream
Odour:	Not available

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Odour threshold:	Non-applicable *
<b>Volatility:</b>	
Boiling point at atmospheric pressure:	165 °C
Vapour pressure at 20 °C:	466 Pa
Vapour pressure at 50 °C:	2595,12 Pa (2,6 kPa)
Evaporation rate at 20 °C:	Non-applicable *
<b>Product description:</b>	
Density at 20 °C:	1400 kg/m <sup>3</sup>
Relative density at 20 °C:	1,392
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	<20,5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
<b>Flammability:</b>	
Flash Point:	25 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	287 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
<b>Explosive:</b>	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
<b>9.2 Other information:</b>	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

- CONTINUED ON NEXT PAGE -





**SECTION 10: STABILITY AND REACTIVITY (continued)**

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION \*\***

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.  
IARC: Xylene (3); Ethylbenzene (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

\*\* Changes with regards to the previous version



**SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)**

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	Route	Toxicity	
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	500 mg/kg	Rat
	LD50 dermal	2500 mg/kg (ATEi)	
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	LD50 oral	1030 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation	Non-applicable	
Salicylic acid CAS: 69-72-7 EC: 200-712-3	LD50 oral	891 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Amines, polyethylenepoly-, triethylenetetramine fraction CAS: 90640-67-8 EC: 292-588-2	LD50 oral	2505 mg/kg	Rat
	LD50 dermal	1465 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat

**Acute Toxicity Estimate (ATE mix):**

ATE mix		Ingredient(s) of unknown toxicity
Oral	1773,53 mg/kg (Calculation method)	68,01 %
Dermal	1478,46 mg/kg (Calculation method)	68,01 %
Inhalation	11,98 mg/L (4 h) (Calculation method)	74,08 %

\*\* Changes with regards to the previous version

**SECTION 12: ECOLOGICAL INFORMATION \*\***

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

Identification	Acute toxicity		Species	Genus
	Route	Toxicity		
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
fatty acids, C16 and C18 unsatd., polymers with bisphenol A, Bu glycidyl ether, epichlorohydrin and triethylenetetramine CAS: 105839-18-7 EC: 600-687-2	LC50	1.8 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0.57 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LC50	646 mg/L (48 h)	Leuciscus idus	Fish
	EC50	400 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	79 mg/L (3 h)	Scenedesmus subspicatus	Algae

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Acute toxicity		Species	Genus
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	LC50	110 mg/L (96 h)	Leuciscus idus	Fish
	EC50	388 mg/L (48 h)	N/A	Crustacean
	EC50	Non-applicable		
Amines, polyethylenepoly-, triethylenetetramine fraction CAS: 90640-67-8 EC: 292-588-2	LC50	330 mg/L (96 h)	Pimephales promelas	Fish
	EC50	31.1 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	20 mg/L (72 h)	Selenastrum capricornutum	Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
fatty acids, C16 and C18 unsatd., polymers with bisphenol A, Bu glycidyl ether, epichlorohydrin and triethylenetetramine CAS: 105839-18-7 EC: 600-687-2	BOD5	Non-applicable	Concentration	2 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	5 %
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	94 %
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	BOD5	Non-applicable	Concentration	7 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	8 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BCF	0.3
	Pow Log	1.1
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	BCF	3
	Pow Log	-0.44
	Potential	Low

**12.4 Mobility in soil:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Absorption/desorption		Volatility	
	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
Xylene CAS: 1330-20-7 EC: 215-535-7	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
	Koc	Non-applicable	Henry	Non-applicable
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3,679E-2 N/m (25 °C)	Moist soil	Non-applicable
	Koc	928	Henry	4,46E-4 Pa·m <sup>3</sup> /mol
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	Conclusion	Low	Dry soil	No
	Surface tension	Non-applicable	Moist soil	No
	Koc	Non-applicable	Henry	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,444E-2 N/m (207,25 °C)	Moist soil	Non-applicable
	Koc	1584	Henry	Non-applicable
Amines, polyethylenepoly-, triethylenetetramine fraction CAS: 90640-67-8 EC: 292-588-2	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
	Koc	520	Henry	798,44 Pa·m <sup>3</sup> /mol
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

\*\* Changes with regards to the previous version

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP6 Acute Toxicity, HP13 Sensitising, HP8 Corrosive

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2019 and RID 2019:

- CONTINUED ON NEXT PAGE -



**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number:** UN2920
- 14.2 UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (fatty acids, C16 and C18 unsatd., polymers with bisphenol A, Bu glycidyl ether, epichlorohydrin and triethylenetetramine; Xylene)
- 14.3 Transport hazard class(es):** 8
- Labels:** 8, 3
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
  - Special regulations: 274
  - Tunnel restriction code: D/E
  - Physico-Chemical properties: see section 9
  - Limited quantities: 1 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 38-16:



- 14.1 UN number:** UN2920
- 14.2 UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (fatty acids, C16 and C18 unsatd., polymers with bisphenol A, Bu glycidyl ether, epichlorohydrin and triethylenetetramine; Xylene)
- 14.3 Transport hazard class(es):** 8
- Labels:** 8, 3
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
  - Special regulations: 274
  - EmS Codes: F-E, S-C
  - Physico-Chemical properties: see section 9
  - Limited quantities: 1 L
  - Segregation group: Non-applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2019:



- 14.1 UN number:** UN2920
- 14.2 UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (fatty acids, C16 and C18 unsatd., polymers with bisphenol A, Bu glycidyl ether, epichlorohydrin and triethylenetetramine; Xylene)
- 14.3 Transport hazard class(es):** 8
- Labels:** 8, 3
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
  - Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Benzyl alcohol.

- CONTINUED ON NEXT PAGE -



**SECTION 15: REGULATORY INFORMATION (continued)**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable  
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
Article 95, REGULATION (EU) No 528/2012: Benzyl alcohol (Product-type 6) ; Salicylic acid (Product-type 2, 3, 4)  
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c		5000	50000
E2		200	500

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ...):**

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**



**SECTION 16: OTHER INFORMATION (continued)**

**COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):**

- New declared substances
    - Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)
    - 2-(4-methylcyclohex-3-en-1-yl)propan-2-ol
  - Removed substances
    - 2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)
    - Terpineol (8000-41-7)
    - Hydrocarbons, terpene processing by-products (68956-56-9)
- CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):
- Substances contained in EUH208:
    - New declared substances
      - Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)
    - Removed substances
      - Hydrocarbons, terpene processing by-products (68956-56-9)

**Texts of the legislative phrases mentioned in section 2:**

H314: Causes severe skin burns and eye damage  
H318: Causes serious eye damage  
H373: May cause damage to organs through prolonged or repeated exposure (Oral)  
H317: May cause an allergic skin reaction  
H411: Toxic to aquatic life with long lasting effects  
H302+H312+H332: Harmful if swallowed, in contact with skin or if inhaled  
H304: May be fatal if swallowed and enters airways  
H226: Flammable liquid and vapour

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 4: H302 - Harmful if swallowed  
Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin  
Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled  
Acute Tox. 4: H312 - Harmful in contact with skin  
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled  
Acute Tox. 4: H332 - Harmful if inhaled  
Aquatic Acute 1: H400 - Very toxic to aquatic life  
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways  
Eye Dam. 1: H318 - Causes serious eye damage  
Eye Irrit. 2: H319 - Causes serious eye irritation  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour  
Flam. Liq. 3: H226 - Flammable liquid and vapour  
Repr. 2: H361d - Suspected of damaging the unborn child.  
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage  
Skin Irrit. 2: H315 - Causes skin irritation  
Skin Sens. 1: H317 - May cause an allergic skin reaction  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation)  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)  
STOT SE 3: H335 - May cause respiratory irritation  
STOT SE 3: H336 - May cause drowsiness or dizziness

**Classification procedure:**

Skin Corr. 1B: Calculation method  
Eye Dam. 1: Calculation method  
STOT RE 2: Calculation method  
Skin Sens. 1: Calculation method  
Aquatic Chronic 2: Calculation method  
Acute Tox. 4: Calculation method  
Asp. Tox. 1: Calculation method  
Flam. Liq. 3: Calculation method (2.6.4.3)

**Advice related to training:**

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

- CONTINUED ON NEXT PAGE -



**SECTION 16: OTHER INFORMATION (continued)**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
 IMDG: International maritime dangerous goods code  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organisation  
 COD: Chemical Oxygen Demand  
 BOD5: 5-day biochemical oxygen demand  
 BCF: Bioconcentration factor  
 LD50: Lethal Dose 50  
 LC50: Lethal Concentration 50  
 EC50: Effective concentration 50  
 Log-POW: Octanol-water partition coefficient  
 Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -