## **PINTURAS JUNO**

# DATA SHEET INDUSTRIAL DIVISION

MARTELE CODE: 5399

#### **DESCRIPTION**

This synthetic metallised enamel is suitable to achieve industrial hammer finishes for indoor surfaces.

### USAGE

Especially suitable as metallic surface finish, such as engines, lift doors, metal fittings, furniture and other metallic accessories.

#### **CHARACTERISTICS**

Finish..... Gloss Colour See colour chart Viscosity..... 50-80" S/FR1002.  $1.10 \pm 0.5$  g/cc as per colour S/FR1001 Density..... Drying time ..... To the touch: 2 hours Second coat..... 24 hours "T" (50707) Diluent..... VOC content..... Max 600 g/l Solids in volume ..... 41% Theoretical, according to colour Theoretical coverage..... 16.25 m<sup>2</sup> / I / coat for 25 dry microns

.../...



#### **SURFACE PREPARATION**

If applied over primers, follow instructions for primer repainting. If applied directly on metal, clean the surface until any dirt or grease traces are removed, as well as oxide residues.

#### **APPLICATION PROCEDURE**

To achieve a special finish effect it must be applied with a spray painting gun.

Dilute with "T" solvent to correct application.



Diluent "T" (50707).



With the same product. Repaint after 24 hours

#### **OBSERVATIONS**

Stir the recipient contents thoroughly until evenly mixed.

MARTELE ENAMEL /2

Date: January 2008/Revision: 1

NB: Our technical instructions and advice, whether oral, in writing or through tests are giv en in good faith and to the best of our knowledge. However, it must only be construed as an indication WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the procedures and purposes intended. The application, use and processing of the products supplied by us are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.

