PINTURAS JUNO

PLASTE MULTIPURPOSE

CODE: 77050

DESCRIPTION

A filler product suitable for hole and fine crack filling, repairing profiles without formwork, repairing and rebuilding cornices, façade sculptures and architectural ornaments, and construction materials joinery such as tiles, ceramics, etc.

USAGE: INDOOR - OUTDOOR

Adherence to all types of substrates: concrete, stone, gypsum, glazed components, tiles, well bonded paints.

CHARACTERISTICS

- White colour. It admits universal colorants.
- Quick hardening. Usage time: 30 minutes at 20° C.
- Quick drying: it can be coated with any type of paint after 24 hours, without any efflorescence or colour change.
- Theoretical coverage: 1Kg/m² on 1 mm coat.
- It can be applied on thin and thick coats without crazing.
- It can be easily moulded and cut.

PASTE PREPARATION

Add 1 kilogram of powder to 0.4 litres of water (6 litres per 15 kg sack).

Mix until an even paste is achieved and apply with a trowel, spatula or a laying trow el. Do not stir once it starts to harden.



APPLICATION PROCEDURE

Surfaces must be dry, clean, healthy and ready to support loads, free from "separating" agents.

Strip any prior outdoor paint and undercoats if in poor condition.

Take into account any pulverous or detachable bases beforehand.

APPLICATION

Trowel, spatula or laying trowel.

CLEANING

Clean any product excess and all tools with water.

PRECAUTIONS

Do not apply in full sun or in temperatures below 5° C.

STORAGE

Store perfectly closed and away from moisture.

SAFETY

Exempt from safety labelling.

PACKAGING

Carton box: Size: 1 kg

Date: July 2000/Revision:

N.B.: Our technical instructions and advice, whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, it must only be construed as an indication **WITHOUT LIABILITY** even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the procedures and purposes intended. The application, use and processing of the products supplied by us are carried out outs ide and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.

