

Technical Datasheet

D-40 for Chlororubber/Pliolite

Prod.Code: 50.000 Thinners



DESCRIPTION

Thinner for JUNO Chlorinated Rubber and Pliolite paints and coatings.
Formulated based on a mixture of high-grade aromatic hydrocarbons.

USE

Use for diluting synthetic coatings, pliolite and chlorinated rubber-based products. For cleaning tools used with the aforementioned types of paints. Do not use with nitrocellulose, epoxy or polyurethane based products. Use only with products where this is recommended in product's technical sheet.

PROPERTIES

- Allows for proper evaporation rate that allows a uniform coating finish
- Gives perfect balance between internal in-coat and surface drying
- Correctly adjusts the viscosity in the indicated paints
- High cleaning and dissolving power

Color: Colourless

Density: 0,87 ± 0,05 g/cc S/FR1001

Flash Point: Non-flammable up to 40 °C

50000 CLEAR



Format: 1L / 5L / 20 L

SURFACE PREPARATION

Proceed as indicated in recommended paint product's technical datasheet

USER TIPS

DILUENT. Add the recommended amount according to the technical sheet of the product to be diluted. Stir the mixture slowly until total homogenization.

CLEANING. Clean tools immediately after use, to prevent the paint from drying out. Thoroughly remove any remains of paint and then wash the equipment with soapy water. Let the tools dry out completely before storage.

SAFETY & ENVIRONMENT

The product must be handled with in a properly ventilated area and with the necessary protection measures. Avoid sources of ignition. Avoid inhalation of product ad its vapour. Avoid contact with skin and eyes, using gloves and protective goggles. In case of splashing, wash with plenty of water. For more information, consult the Safety Data Sheet.

Store the excess material in a ventilated and dry place. Close containers carefully and keep upright to avoid spills. Preserve the containers of frost, high temperatures and direct exposure to the sun.

Do not eat, drink or smoke during the preparation and application of the product. Keep out of the reach of children.

Do not discharge into drains or the environment. Dispose of at an authorized waste collection point.

Consult your local council for correct recycling of both the container, waste and surplus products according to the law and principles of environmental respect.

The information contained in this data sheet may change and must be updated. Consult www.junopaints.com or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.