

Technical Datasheet

JUNODECO

Code: 72330 Interior/Monocoat



DESCRIPTION

High opacity decorative interior emulsion. Contains anti-mold preservatives. Easy application and quick drying properties giving a matt finish. Also ideal for quick turnover of rooms and spaces such as hotels, rental apartments, children's rooms etc.

Recommended for decoration of indoor environments with smooth matt finish of high quality and where protection against the proliferation of microorganisms and mold is required.

PROPERTIES

- Consistent one-coat system
- One coat of JUNODECO is equivalent to two coats of conventional emulsion. (Average values may vary depending on the texture and absorption)
- Saves application time
- Permits use of painted areas and spaces in very short time
- Proper color chart
- Colors with maximum coverage, opacity and color-stability
- Reduces proliferation of fungi, mold and other microorganisms
- Great resistance
- Washable
- Transpiring
- Includes a built-in roller grid

Finish: Matt

Color: White and Junodeco color chart

Viscosity: Min. 110 P S/FR1007

Density: 1,56 ± 0,05 g/cc S/FR1001 (color dependant)

Drying: Touch dry min. 25 minutes

Min. repaint time: 4 hours

Max. repaint time: 12 hours

Diluent: Ready to use. Do not dilute

Performance: 10 m²/L (per coat)

Average observed values. Depending on surface absorption and texture.

Flash Point: Not flammable

VOC Content: Máx. 10 g/l

72330 BLANCO (WHITE)	72331 MAÍZ (CORN)
72332 MOSTAZA (MUSTARD)	72333 ARENA (SAND)
72334 MELOCOTÓN (PEACH)	72335 CANELA (CINNAMON)
72336 LINO (LINEN)	72337 BEIGE
72338 LILA (LILAC)	72339 LAVANDA (LAVENDER)
72340 MORA (BLACKBERRY)	72341 LUNA (MOON)
72342 PIEDRA (STONE)	72343 ANTRACITA (ANTRACITE)
72344 CALABAZA (PUMPKIN)	72345 BERMELLÓN (VERMILLION)
72346 PERA (PEAR)	72347 MANZANA (APPLE)
72348 HELECHO (FERN)	72349 MAGENTA
72350 BERENJENA (EGGPLANT)	72351 CELESTE (LIGHT BLUE)
72352 AZUL ((BLUE)	72353 ZAFIRO (SAPPHIRE)
72354 FRESA (STRAWBERRY)	72355 CEREZA (CHERRY)



Format: 2,5 L / 4 L

The information contained in this data sheet may change and must be updated. Consult www.junopaints.com or your nearest JUNO representative for the latest data sheet. The application technical advice, whether verbal, written or by trial, is based on JUNO's experience and technical knowledge. The data shown in this document should be considered a recommendation and as such does not imply any commitment, including with regard to possible industrial property rights of third parties. The application, the use and the transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the customer, applicator or manipulator of the products and not the supplier company. This document does not exempt the customer from conducting their own examination of the products supplied, in order to verify their suitability for the intended procedures and purposes. In the event of liability assumed by JUNO, this will be limited to the strict value of the merchandise supplied and used by the customer, whatever the damages caused. JUNO guarantees the quality of all its products, in accordance with the General Conditions of Sale in force.

Technical Datasheet

JUNODECO

Code: 72330 Interior/Monocoat



JUNO

SURFACE PREPARATION

NEW SURFACES. On new, firm, clean and dry surfaces, no preparation of the support is necessary. In case of requiring greater consistency and adhesion of the surface, prime using **Hidrocril (Prod. Code 81.006)** diluted to 1 part Hidrocril : 4 parts of water.

For projected plasters, to eliminate occasional differences in absorption, it is recommended to seal surfaces with **Aquasell (Prod.Code 21.203)**.

PAINTED SURFACES. If the paint is in good condition apply the product directly. For cracked, peeling paint in bad condition, remove loose parts and flakes and eliminate dust and dirt. go over and repair faulty areas, fissures, cracks and irregularities using **Juno Plaster (Prod. Code 77.000)** before painting.

When presence of gloss or satin paint, it is necessary to surface sand until any gloss is removed to promote adhesion and eliminate surface tensions. Perform a testpatch to check the solidity and anchorage of the paint and to prevent possible incompatibilities between layers before proceeding with the work.

PATHOLOGIES.

Mold contamination. Wash well and disinfect area using **Junoclean (Prod. Code 760.180)** Rinse with clean water and leave to dry completely. Coat using anti-mould paint or add **Misky-Misky (Prod. Code 79.597)**.

Salt Efflorescence (Saltpeter). Brush thoroughly, wash and neutralize using a chloric-acid or zinc sulphate solution (10%) mixed with water. Rinse well and leave to dry completely before proceeding with primer/sealer (as above) and paint.

Humidity, grease, smoke or nicotine stains, etc. Wash well with water and detergent, dejar secar completamente. Rinse with clean water and leave to dry completely. Prime with **Tapa-Manchas (Stain cover) (Prod.Code 21.350)**.

APPLICATION METHOD

Stir paint well before use, ensuring complete homogenization.

Apply on consistent, clean, completely dry surfaces, free of efflorescence (saltpeter) and molds.

Do not apply to substrates with a temperature less than 5 ° C or excessively hot.

It is convenient to protect areas that are not to be painted (plugs, skirting boards, floor, door frames and windows) with painter's tape and paper. Once the work is complete remove the tape to prevent paint from lifting later on.

DILUTION. Product is ready to use. Do not dilute. For using as undercoat/primer, product can be diluted up to a maximum 25%. (based on avg. values and surface porosity, texture and adhesion)

APPLICATION METHOD. Apply using brush, roller or spray equipment.

CLEANING. Remove as much product as possible from equipment before cleaning.

Replace lid firmly. Clean equipment and stains immediately after use with warm soapy water and rinse thoroughly.

SAFETY & ENVIRONMENT

Minimize product waste by estimating the correct amount needed, taking into account the m2, porosity and texture of the substrate.

Replace lid firmly, and keep upright to avoid spills. Store surplus material in a ventilated, dry place. The container must be clean and of adequate size for the quantity of product left over.

Preserve containers away from frost, high temperatures and direct exposure to the sun.

Do not eat, drink or smoke while preparing and applying the product.

Surface preparation and application operations must be carried out with appropriate safety and protective equipment.

Keep out of reach of children

Dispose of contents/container to an authorized waste disposal site in accordance with local/national regulations.

Ensure good ventilation during application and drying.

Do not get in eyes, on skin, or on clothing

IF SWALLOWED: Call a doctor or hospital/poison centre if you feel unwell.

For more information consult product's Material Safety Data Sheet.

The information contained in this data sheet may change and must be updated. Consult www.junopaints.com or your nearest JUNO representative for the latest data sheet.

The application technical advice, whether verbal, written or by trial, is based on JUNO's experience and technical knowledge. The data shown in this document should be considered a recommendation and as such does not imply any commitment, including with regard to possible industrial property rights of third parties. The application, the use and the transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the customer, applicator or manipulator of the products and not the supplier company. This document does not exempt the customer from conducting their own examination of the products supplied, in order to verify their suitability for the intended procedures and purposes. In the event of liability assumed by JUNO, this will be limited to the strict value of the merchandise supplied and used by the customer, whatever the damages caused. JUNO guarantees the quality of all its products, in accordance with the General Conditions of Sale in force.