PINTURAS JUNC DATA SHEET

PLASTE JUNO POWDER

CODE: 77000

DESCRIPTION

An indoor filler for adequate preparation of substrates prior to painting or papering.

USAGE: INDOOR

Suitable for making good small imperfections such as cracks, wire chases, etc.

Excellent wood sealant.

Suitable to create decorative finishes on fresh plaster, achieving textured effects with the aid of decoration rollers or other implements.

CHARACTERISTICS

• Fine white powder.

Apparent density 0.70 g/cc approx.

Usage time Approx. 2 hours

Drying time Variable according to thickness

Repainting Minimum 24 hours

Theoretical coverage 1 m² of 1 mm coat, for every 700 g of powder.

Very easy to sand down

Excellent hardness, adherence and cohesion.

SUBSTRATE PREPARATION

Substrates must be clean, dry and free of dust, grease and wax.

Remove the dust and clean the surface to be treated. Isolate and protect metallic parts with **White Multipurpose Primer** or other anti-corrosive primer.

If the base is very absorbent or disintegrated, prime with **Hidrocril Acrylic Emulsion** thinned with 1 part Hidrocril and 4 parts of water.



APPLICATION PROCEDURE

Prepare the paste with 2 parts of powder and 1 part of water. Blend vigorously to obtain a soft and consistent paste and use immediately. This filler can be used for approximately 2 hours at 20°C. Apply with a flat trowel or spatula.

OBSERVATIONS

Clean all tools with water.

Store perfectly closed and away from moisture. Do not apply in room temperatures below 5° C.

PACKAGING

1 kg and 5 kg boxes, and 15 kg sacks.

Date: July 2000/Revision: 3

N.B.: Our technical instructions and advice, whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, it must only be construed as an indication WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the procedures and purposes intended. The application, use and processing of the products supplied by us are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.

