

**TECHNICAL DATA SHEET**

**JUNOREV TEXTURED MASONRY COATING**

Code: 64.500

JANUARY 2015

**DESCRIPTION**

Junorev Textured masonry coating is a professional quality exterior emulsion paint. It has an attractive high build finish and provides excellent coverage and application.

Junorev is based on water- dispersed pure acrylic resins. This product is waterproof and permeable to water vapor and provides exterior durability and protection even in harsh and demanding environments.

Protects concrete surfaces against carbonation and presents excellent adherence and external performance properties.

Excellent resistance to the levels of atmospheric humidity normally experienced in exterior environments

**USE: INTERIOR - EXTERIOR**

Product conceived to protect and decorate exterior mineral surfaces, hence provides excellent resistance to mild atmospheric fume attack and to the salts in new mortar, rendering and similar surfaces.

Can also be used for painting decking in sport facilities.

**APPLICATION INSTRUCTIONS**

- Brush, roller or spray gun. - Pneumatic equipment.
- Stir the recipient contents thoroughly until evenly mixed.
- Apply on clean, dry and consolidated surfaces. On previously painted surfaces, if the existing paint is gloss, satin, or elastic, tensions may occur resulting in cracks or fissures.
- As with other water-based paints, do not apply in temperatures below 5°C or overly heated surfaces.

**PREPARATION**

For all types of substrate:

In case of mould, fungal, algae or other parasite contaminations, take the following steps:

- Wash with 10% bleach and water solution.
- Rinse with water.
- Allow to dry thoroughly before painting.
- Prime with Junosan Base Cleaner.
- Use ANTI-MOULD products.

If saline efflorescence (saltpetre) is found:

- Brush and wash with 10% Hydrochloric Acid or 10% Zinc Sulphate solution.
- Rinse with water.
- Allow to dry thoroughly before painting.

These operations must be carried out under appropriate safety conditions

Dying: With Junoral Water Colorant, not exceeding 3% of colorant.

**APPLICATION PROCEDURE**

SUBSTRATE	PREPARATION	APPLICATION	
		INTERIOR	EXTERIOR
Concrete, cement or mortar based on NEW hydraulic binders.	Cleaning Efflorescence removal	* 1 Coat of Akril 80 varnish or Junolite. * 2 Coats of Junorev Tex. diluted with 10% water	* 1 Coat of Akril 80 varnish ir JunoLite * 2 Coats of Junorev Tex. diluted with 10% water
Non-pulverous old paints	Cleaning and/or washing	* 2 Coats of Junorev Tex. with 10% water	* 2 Coats of Junorev Tex. diluted with 10% water
Old pulverous paints	Cleaning. Fix	* 1 Coat of Hidrocril diluted. * 2 Coats of Junorev Tex. diluted with 10% water	* 1 Coat of Hidrocril diluted. * 2 Coats of Junorev Tex. diluted with 10% water
Old paint in poor condition.	Remove. Sandblast or JUNO paint-remover	Same as new surfaces	* Same as new surfaces
Plaster, gypsum	Cleaning. Fix if necessary	* 1 Coat of Hidrocril diluted. * 2 Coats of Junorev Tex. diluted with 10% water	* Not recommended.

The information contained in this data sheet may vary and must be updated. Please visit [www.juno.es](http://www.juno.es) or consult with your nearest JUNO representative who will provide you with the most recent date sheet. Our technical instructions and advice whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, they must only be interpreted as indications WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the intended procedures and purposes. The application, use and processing of the products supplied by JUNO are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.

Finish: Textured

Color: NCS & RAL

Viscosity: Min 350 Poises S/FR1007

Density: 1.80 +/-0.05 S/FR1001

Volume Solids: 58% (±2%) Theoretical

Drying time: 2-4 hours to the touch  
 Repaint minimum 24 hours.  
 Maximum: undefined.

Diluent: Water

Coverage: Approx. 1 m<sup>2</sup>/l.

VOC's content: maximum 30g/l.

Health & Safety: Aqueous-phase paint  
 product: Exempt from labelling

Water vapour permeability: Sd=0.3489 m  
 (ISO 7783:2012)

Water permeability: w= 0.0191 kg/  
 (m<sup>2</sup>.h0.5) (UNE-EN: 1062-3-2008)

CO2 permeability: Sd=83 +/- 4 m (UNE-  
 EN:16062-6:2003)

## TECHNICAL DATA SHEET

## JUNOREV TEXTURED MASONRY COATING

Code: 64.500

## APPLICATION RECOMMENDATIONS

Surfaces must be clean of dust, grease, oils, dirt, rust, waste or anything else that may contaminate the paint. Remove the paint, varnishes or old treatments in a poor state and if needed clean up the imperfection, area and exposition with an adequate filler. Shake the container before application to homogenize the paint and the color. Respect the recommended application temperature and the drying times between coats (20°C, relative humidity 65%). The thickness of application, temperature and humidity may affect drying times. Buy only the necessary quantity required, taking into account the m<sup>2</sup>, porosity and support texture. Store the remaining product in a dry and well-ventilated place. Work with the appropriate ventilation and respect the safety precautions norms indicated in the safety data sheet of the product.

## CLEANING

Clean the splash and stains immediately with soap water or with an adequate solvent. Clean tools after use (brushes, rollers, pencils, machines etc.) and let them dry before storing. Consult your town council about the appropriate recycling method for the container, waste and excess paint, in accordance with the existing legislation and environmental protection principles.

## SHIPPING



**Packaging:** 04/15 liters  
**Shipping Weight:**  
**Units per pallet:** 120/33



**Freight Classification:**  
Paint or paint related material



**Transport Information**  
No restriction for transport (ADR/RID, IMDG, IATA)

The information contained in this data sheet may vary and must be updated. Please visit [www.juno.es](http://www.juno.es) or consult with your nearest JUNO representative who will provide you with the most recent data sheet. Our technical instructions and advice whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, they must only be interpreted as indications WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the intended procedures and purposes. The application, use and processing of the products supplied by JUNO are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.